

AVALON® Floor

Easy-to-clean Coating for Floors

Features and technical data

Features:

- Fits to most floor materials, for example parquet and tiles (excl. unprocessed wood)
- Easy-to-clean properties
- Good weather and wear resistance
- Quick and easy application

Technical data:

- **Appearance:** clear colourless liquid
- **Dilution:** ready to use
- **Typical consumption:** 60-100 m² / l (depending on the surface)



Composition and function

Avalon® Floor generates a transparent and hard film coating on the substrate.

Coating changes surface properties so that surface becomes water and oil repelling. The surface can be cleaned more quickly and with lower cleaning expenses and effort.

Coating tolerates well chemicals and mechanical abrasion.

Storage

Solution should be stored at room temperature in a well ventilated place. Keep containers tightly closed.

Storing time is 12 months from the date of manufacture.

Instructions for use

See MSDS before starting. During work please wear goggles, mask and gloves for safety. It is recommendable to test coating on a small area only to make sure that painting colours do not fade.

Cleaning

The substrate has to be oil/grease- and dust-free. Cleaning can be done with a suitable cleaning agent, which doesn't leave residues. Surface has to be dry before coating.

Coating

Apply by mopping with wet mop containing the coating solution until the whole surface is moist. Be sure not to leave wiping traces.

Curing

Curing takes place after 1 hour at room temperature. The final mechanical properties are achieved after about 24 hours, chemical tolerance after 1 week.